

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-11 (canceled).

12. (currently amended) A run-flat device for fitting on the outer circumferences of a wheel inside an inflatable tyre, said device comprising an annular ring made up of a plurality of arcuate segments having a flange at each end that overlaps circumferentially the corresponding flanges of adjacent segments, which flanges are interconnected by clamping means equally spaced around the ring that imparts to each segment a circumferential clamping force and an axial clamping force to urge the segments circumferentially and axially towards each other wherein the clamping means comprises a first and second clamping bolts which pass through a pair of spaced holes formed in the adjacent flanges, said device ~~additional~~ additionally comprising a retaining plate having two captive nuts mounted thereon, for securing the first and second clamping bolts and to prevent lateral twisting of the flanges, and a clamping plate spaced remotely from said retaining plate and shaped so as not to interfere with one of said clamping bolts.

13. (currently amended) A run-flat device according to claim 12 wherein the clamping means further comprises a slot provided in one of the flanges at one end of each segment that includes an inclined surface that faces away from the immediately adjacent segment, a wedge provided in the slot, said wedge having an inclined surface that contacts the inclined surface of the slot, and having a hole that aligns with a first hole of the pair of spaced holes in the flanges, ~~and a first~~ such clamping bolt that passes through the first hole of the pairs of holes and the hole in the wedge whereby tightening of the said first bolt causes the wedge to urge the segments towards each other circumferentially, and the clamping means further includes a ~~the~~ second such clamping bolt substantially parallel to the first bolt, said second bolt passing through the second

hole of the pair of holes in the flanges and through a said clamping plate in contact with a side face of the segment whereby tightening of the second bolt clamps the flanges of the segments together axially, and the combined clamping effect of the two bolts restricts pivotal movement of the segments relative to each other.

14. (previously presented) A run-flat device as claimed in claim 13 wherein the captive nuts are located within the first and second holes.

15. (previously presented) A run-flat device according to claim 12 wherein there is provided a split inner sleeve for fitment to the rim of the wheel and onto the outer circumference of which the segments sit.

16. (previously presented) A run-flat device according to claim 13 wherein there is provided a split inner sleeve for fitment to the rim of the wheel and onto the outer circumference of which the segments sit.

17. (previously presented) A run-flat device according to claim 14 wherein there is provided a split inner sleeve for fitment to the rim of the wheel and onto the outer circumference of which the segments sit.

18. (previously presented) A run-flat device according to claim 15 wherein the inner circumference of the inner sleeve is profiled to match the profile of the outer circumference of the wheel.

19. (previously presented) A run-flat device according to claim 16 wherein the inner circumference of the inner sleeve is profiled to match the profile of the outer circumference of the wheel.

20. (previously presented) A run-flat device according to claim 17 wherein the inner circumference of the inner sleeve is profiled to match the profile of the outer circumference of the wheel.

21. (previously presented) A run-flat device according to claim 15 wherein the outer circumference of the inner sleeve has a recess, and each segment has a flange on its inner circumferential surface that engages in the recess on the inner sleeve.

22. (previously presented) A run-flat device according to claim 16 wherein the outer circumference of the inner sleeve has a recess, and each segment has a flange on its inner circumferential surface that engages in the recess on the inner sleeve.

23. (previously presented) A run-flat device according to claim 17 wherein the outer circumference of the inner sleeve has a recess, and each segment has a flange on its inner circumferential surface that engages in the recess on the inner sleeve.

24. (currently amended) A run-flat device according to ~~claim 13~~ claim 15 wherein the inner sleeve comprises a central band and two side bands made of a material that is more resilient than the material of the central band.

25. (canceled)

26. (canceled)

27. (previously presented) A run-flat device according to claims 24 wherein the central band is made of nylon.

28. (previously presented) A run-flat device according to claim 24 wherein the side bands are made of polyurethane.

29. (canceled)

30. (previously presented) A run-flat device according to claim 12 wherein the segments are identical in shape.

31. (previously presented) A run-flat device according to claim 13 wherein the segments are identical in shape.

32. (previously presented) A run-flat device according to claim 14 wherein the segments are identical in shape.

33. (canceled)

34. (canceled)

35. (previously presented) A run-flat device according to claim 15 wherein a shear pin is provided between the inner sleeve and each of the segments to resist circumferential movement of the sleeves relative to the inner sleeve during normal running of the wheel.